

# TR 135

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>13.6 - 36</b>   |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRACTOR / ANHÄNGER |
| <b>VERSION</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TT                 |
| <b>LI/SS</b>     | 121 A8             |



## ABMESSUNGEN US STANDARD

|                 |          |                                      |                |
|-----------------|----------|--------------------------------------|----------------|
| <b>USA-CODE</b> | 94003358 | <b>RIM ALT</b>                       | W 11           |
| <b>OD (IN)</b>  | 59.6     | <b>ECE</b>                           | E4-106R-002036 |
| <b>SLR (IN)</b> | 28.1     | <b>PR</b>                            | 6              |
| <b>RC (IN)</b>  | 184.5    | <b>TRA CODE</b>                      | R1             |
| <b>RIM REC</b>  | W 12     | <b>TREAD DEPTH (32<sup>nd</sup>)</b> | 44.73          |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>22</b> |
| 25               | 3200      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.