

AGRIMAX RT 765

TIRE SIZE	650/75 R 38
UM	IS STANDARD
MACHINERY	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	169 D



DIMENSIONS IS STANDARD

SW (MM)	655	RIM ALT	DW 20 B ; DW 23 B
OD (MM)	1941	ECE	E11-106R-006161
SLR (MM)	874	SRI	925
RC (MM)	5820	TRA CODE	R1W
RIM REC	DW 21 B	TREAD DEPTH (MM)	58

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2730	3135	3600	4060	4525	4990	5455	5800
50	2865	3290	3780	4265	4755	5240	5725	6090
40	2990	3435	3945	4450	4960	5470	5975	6355
30	3135	3605	4140	4670	5205	5740	6270	6670
10 LT	3655	4200	4825	5445	6065	6690	7310	7775
10 HT	3135	3605	4140	4670	5205	5740	6270	6670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.