


AGRIMAX V-FLECTO



TIRE SIZE	VF 900/60 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	187 D

DIMENSIONS US STANDARD

USA CODE	94075096	RC (IN)	238.3
SW (IN)	34.7	RIM REC	DW 30 B
OD (IN)	80.5	ECE	E11-106R-009004
SLR (IN)	34.7	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	9580	11140	12910	14470	16040	17600	19550
FROM 40 TO 25	10530	12250	14190	15910	17620	19340	21490
20	10740	12490	14460	16210	17970	19730	21920
12	10950	12730	14750	16530	18320	20120	22350
5	11570	13470	15600	17490	19380	21270	23640
*UPTO 5 CYC WITH FRONT LOADER	14740	17140	19850	22270	24670	27080	30090
5 HT	10740	12490	14460	16210	17970	19730	21920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.