


# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>280/85 R 28</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS                    |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 118 A8/B   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94021543 | <b>RC (IN)</b> | 140.1          |
| <b>SW (IN)</b>  | 11.5     | <b>RIM REC</b> | W 10           |
| <b>OD (IN)</b>  | 46.7     | <b>RIM ALT</b> | W 9            |
| <b>SLR (IN)</b> | 21.5     | <b>ECE</b>     | E4-106R-000614 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 1610 | 1860 | 2130 | 2390 | 2660 | 2910 |
| 25        | 1610 | 1860 | 2130 | 2390 | 2660 | 2910 |
| 20        | 1720 | 2010 | 2280 | 2570 | 2840 | 3120 |
| 5 LT      | 2150 | 2500 | 2850 | 3210 | 2560 | 3900 |
| 5 HT      | 1720 | 2010 | 2280 | 2570 | 2840 | 3120 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.