

# TR 135

|                     |                   |
|---------------------|-------------------|
| <b>TYRE SIZE</b>    | 23.1 - 26         |
| <b>UM</b>           | IS STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | TRACTOR / TRAILER |
| <b>VERSION</b>      | HD                |
| <b>TYRE TYPE</b>    | TT                |
| <b>LI/SS</b>        | 159 A6            |



## DIMENSIONS IS STANDARD

|                 |      |                 |                  |
|-----------------|------|-----------------|------------------|
| <b>SW (MM)</b>  | 587  | <b>RIM REC</b>  | DW 20 B; DW 20 A |
| <b>OD (MM)</b>  | 1585 | <b>PR</b>       | 16               |
| <b>SLR (MM)</b> | 700  | <b>SRI</b>      | 750              |
| <b>RC (MM)</b>  | 4615 | <b>TRA CODE</b> | R1               |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.30</b> |
| 30                | 4375        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.