


# EARTHMAX SR 55

<b>TIRE SIZE</b>	<b>29.5 R 29</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BULDOZER / BASCULARE ÎNCĂRCĂTURI (LHD) / ÎNCĂRCĂTOR
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	223 A2



## DIMENSIUNI IS STANDARD

<b>OD (MM)</b>	2009	<b>RIM ALT</b>	24.00/3.5; 26.00/3.5
<b>SLR (MM)</b>	911	<b>TRA CODE</b>	L5S
<b>RC (MM)</b>	6047	<b>STAR RATING</b>	★★★
<b>RIM REC</b>	25.00/3.5		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00
10	19500	20000	20600	21200	22400	23000	23600	24300	25000	25750	26500	26500	27250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.