


# EARTHMAX SR 22

<b>TIRE SIZE</b>	<b>20.5 R 25</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	NIVELEUSE / CHARGEUR / BULLDOZER / CHARGEUR / BULLDOZER / NIVELEUSE
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	161 A8 ; 186 A2



## DIMENSIONS IS STANDARD

<b>OD (MM)</b>	1490	<b>RIM ALT</b>	17.00/1.7
<b>SLR (MM)</b>	640	<b>TRA CODE</b>	G2/L2
<b>RC (MM)</b>	4315	<b>STAR RATING</b>	★
<b>RIM REC</b>	17.00/2.0		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00
40	2430	2800	3150	3450	3875	4125	4375	4625	-	-	-	-	-
10	-	-	-	-	-	-	-	-	8000	8250	8750	9000	9500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.