


# AGRIMAX FORCE

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>IF 600/70 R 30</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | HARVESTER / HIGH-POWER TRACTOR<br>/ TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 165 D  |



## DIMENSIONS US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94045211 | <b>RC (IN)</b> | 189.0            |
| <b>SW (IN)</b>  | 23.7     | <b>RIM REC</b> | DW 21 B; DW 21 A |
| <b>OD (IN)</b>  | 63.1     | <b>RIM ALT</b> | DW 20 A; DW 20 B |
| <b>SLR (IN)</b> | 27.9     | <b>ECE</b>     | E11-106R-006495  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI            | 9    | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|----------------------|------|-------|-------|-------|-------|-------|-------|-------|
| 45                   | 4850 | 5570  | 6390  | 7230  | 8050  | 8870  | 9700  | 10330 |
| <b>FROM 40 TO 25</b> | 5330 | 6130  | 7030  | 7950  | 8850  | 9750  | 10670 | 11400 |
| 20                   | 5540 | 6370  | 7310  | 8260  | 9200  | 10140 | 11090 | 11810 |
| 12                   | 5750 | 6610  | 7590  | 8580  | 9560  | 10530 | 11520 | 12260 |
| 5                    | 6770 | 7780  | 8930  | 10090 | 11230 | 12380 | 13550 | 14420 |
| <b>UPTO 20 CYC</b>   | 6930 | 7960  | 9140  | 10330 | 11500 | 12680 | 13870 | 14760 |
| <b>UPTO 10 CYC</b>   | 8270 | 9490  | 10890 | 12310 | 13710 | 15110 | 16530 | 17590 |
| <b>UPTO 5 CYC</b>    | 9060 | 10420 | 11950 | 13500 | 15050 | 16580 | 18130 | 19300 |
| 5 HT                 | 5540 | 6370  | 7300  | 8260  | 9200  | 10140 | 11090 | 11800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.