DATA SHEET

PRINTED ON
23-04-2026

MP 567

TIRE SIZE	**11.5/80 - 15.3**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO / VEICULO UNIVERSAL
VERSÃO	IMPLEMENT
TIRE TYPE	TL
LI/SS DRIVE WHEEL	130 A8
LI/SS FREE ROLLING	143 A8

DIMENSÕES US STANDARD

CÓDIGO USA	94057603	**RC (IN)**	101.5
SW (IN)	11.5	**RIM REC**	9.0
OD (IN)	34.2	**ECE**	E11-106R-003392
SLR (IN)	15.5	**PR**	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	87
25 FR	6010
25 DW	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..