

# EARTHMAX SR 46

|           |                          |
|-----------|--------------------------|
| TIRE SIZE | 30.00 R 51               |
| UM        | US STANDARD              |
| MACHINERY | САМОСВАЛ С ЖЕСТКОЙ РАМОЙ |
| VERSION   | STANDARD                 |
| TIRE TYPE | TL                       |
| LI/SS     | 230 B                    |



## РАЗМЕРЫ US STANDARD

|          |          |             |           |
|----------|----------|-------------|-----------|
| USA CODE | 94074754 | RIM REC     | 22.00/4.5 |
| OD (IN)  | 114.0    | TRA CODE    | E4        |
| SLR (IN) | 51.2     | STAR RATING | ★★        |
| RC (IN)  | 346.5    |             |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 56800 | 58400 | 61500 | 64000 | 66000 | 68000 | 69500 | 71500 | 74000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.