


# RIDEMAX IT 697 (M+S)

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>540/65 R 30 IND</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 156 D ; 161 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 530  | <b>RIM REC</b> | W 16 L          |
| <b>OD (MM)</b>  | 1464 | <b>RIM ALT</b> | W 18            |
| <b>SLR (MM)</b> | 672  | <b>ECE</b>     | E11-106R-003015 |
| <b>RC (MM)</b>  | 4445 | <b>SRI</b>     | 700             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  |
|------------|------|------|------|------|------|------|
| 65         | 1880 | 2320 | 2720 | 3160 | 3560 | 4000 |
| 50         | 2030 | 2505 | 2940 | 3415 | 3845 | 4320 |
| 40         | 2175 | 2685 | 3145 | 3655 | 4115 | 4625 |
| 30         | 2255 | 2785 | 3265 | 3790 | 4270 | 4800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.