DATA SHEET

PRINTED ON
22-04-2026

MT 612

TIRE SIZE	**14.00 - 20**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	TRAILER / IMPLEMENTS / UNIVERSAL VEHICLE
VERSION	STANDARD
TIRE TYPE	TT

DIMENSIONS US STANDARD

USA CODE	94036585	**RC (IN)**	150.7
SW (IN)	15.4	**RIM REC**	10
OD (IN)	49.8	**PR**	22
SLR (IN)	23.4		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	125
50 LS	11680
50 LD	10470

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..