


AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 230/95 R 40 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPRAYER / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 132 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 228 | RIM REC | W 7 |
| OD (MM) | 1454 | RIM ALT | W 8 |
| SLR (MM) | 690 | ECE | E11-106R-004066 |
| RC (MM) | 4445 | SRI | 700 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|-----|------|------|------|------|------|------|------|------|------|
| 50 | 820 | 1060 | 1280 | 1420 | 1500 | 1640 | 1780 | 1900 | 2000 | - |
| 40 | 820 | 1060 | 1280 | 1420 | 1500 | 1640 | 1780 | 1900 | 2000 | - |
| 30 | 880 | 1135 | 1370 | 1520 | 1605 | 1755 | 1905 | 2035 | 2140 | - |
| 10 | 930 | 1170 | 1440 | 1710 | 1980 | 2040 | 2280 | 2520 | 2760 | 3000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.