

# AW 09

<b>TIRE SIZE</b>	<b>380/55 - 17</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	OUTILLAGE AGRICOLE / REMORQUE / PRESSE À PAILLE / MOISSONNEUSE / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	125 A8
<b>LI/SS FREE ROLLING</b>	138 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	390	<b>RIM REC</b>	13.00
<b>OD (MM)</b>	850	<b>ECE</b>	E4-106R-000379
<b>SLR (MM)</b>	377		
<b>RC (MM)</b>	2491		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.80
10 FR	3305
25 FR	2810
30 FR	2645
40 FR	2360
10 DW	2310
25 DW	1965
30 DW	1850
40 DW	1650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.