

AGRIMAX RT 765

TIRE SIZE	620/70 R 42
UM	US STANDARD
MACHINERY	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	166 D



DIMENSIONS US STANDARD

USA CODE	94063505	RIM ALT	DW 18 L
SW (IN)	24.6	ECE	E11-106R-005998
OD (IN)	76.2	TRA CODE	R1W
SLR (IN)	34.5	TREAD DEPTH (32nd)	72.45
RC (IN)	228.4	TMPH (IS) (TKM/H)	0
RIM REC	DW 20 B		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	5500	6320	7250	8180	9120	10050	10990	11680
30	5780	6640	7620	8600	9580	10560	11540	12270
25	6020	6910	7940	8960	9990	11010	12040	12800
20	6320	7260	8330	9410	10480	11560	12630	13440
5 LT	7360	8470	9720	10970	12220	13480	14730	15660
5 HT	6320	7260	8330	9410	10480	11560	12630	13440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.