DATA SHEET

PRINTED ON
23-04-2026

RT 747 AGRO INDUSTRIAL

TIRE SIZE	**11L R 16**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	KOMPAKTLADER / TELESKOPLADER / KOMPAKTLADER / TELESKOPLADER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	122 A8/B

ABMESSUNGEN US STANDARD

USA-CODE	94062737	**RC (IN)**	98.3
SW (IN)	11.4	**RIM REC**	W 8
OD (IN)	33.5	**RIM ALT**	W 10 L
SLR (IN)	14.6	**ECE**	E11-106R-005769

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	32	35	38
5	2790	3370	3950	4230	4530	4850
15	2070	2570	3050	3310	3550	---
25	1940	2390	2850	3080	3310	---

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..