


EARTHMAX SR 35

| | |
|---------------------|--|
| TIRE SIZE | 750/65 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CHARGEUR / CHARGEUR- TRANSPORTEUR LHD / CHARGEUR |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 209 A2 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|--------------------|---------------------|
| CODE USA | 94071340 | RIM REC | 24.00/3.0 |
| OD (IN) | 63.0 | RIM ALT | 22.00/3.0;25.00/3.0 |
| SLR (IN) | 28.1 | TRA CODE | L3 |
| RC (IN) | 189.1 | STAR RATING | ★★ |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73 | 76 | 80 | 83 | 87 | 91 |
|-----------|-------|-------|-------|-------|-------|-------|
| 5 | 34200 | 35300 | 36400 | 37500 | 38600 | 40800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.