


# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>340/85 R 48</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 D ; 154 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94059287	<b>RC (IN)</b>	219.4
<b>SW (IN)</b>	13.9	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	70.7	<b>RIM ALT</b>	W 11
<b>SLR (IN)</b>	33.7	<b>ECE</b>	E11-106R-005765

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	20	23	29	35	41	46	52	58	64
40	3270	3660	4110	4500	4950	5260	5790	6240	6620	7000	7610
30	3440	3840	4320	4720	5200	5520	6070	6560	6960	7350	7990
25	3560	3970	4460	4880	5380	5710	6280	6780	7200	7610	8270
20	3770	4210	4730	5170	5700	6040	6660	7190	7620	8060	870
5	4920	5480	6160	6730	7420	7880	8670	9360	9930	10500	11410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.