


AGRIMAX V-FLECTO



| | |
|---------------------|--|
| TIRE SIZE | VF 710/60 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HIGH-POWER TRACTOR / TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 173 D |

DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 710 | RIM REC | DW 25 B |
| OD (MM) | 1930 | RIM ALT | DW 23 B; MW 25 B |
| SLR (MM) | 860 | ECE | E11-106R-002998 |
| RC (MM) | 5786 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|---------------------------------------|------|------|------|------|------|------|
| 70 | 3250 | 3785 | 4315 | 4850 | 5380 | 5915 |
| FROM 65 TO 40 | 3575 | 4160 | 4745 | 5330 | 5915 | 6500 |
| 30 | 3645 | 4240 | 4835 | 5435 | 6030 | 6630 |
| 20 | 3715 | 4325 | 4930 | 5540 | 6150 | 6760 |
| 10 | 3930 | 4575 | 5215 | 5860 | 6505 | 7150 |
| *UPTO 10 CYC WITH FRONT LOADER | 5005 | 5820 | 6640 | 7460 | 8280 | 9100 |
| 10HT | 3645 | 4240 | 4835 | 5435 | 6030 | 6630 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.