


AGRIMAX V-FLECTO

TIRE SIZE	VF 650/85 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	182 D



ABMESSUNGEN US STANDARD

USA-CODE	94513529	RC (IN)	240.9
SW (IN)	26.4	RIM REC	DW 23 B
OD (IN)	81.5	RIM ALT	DW 20 B; DW 21 B
SLR (IN)	34.9	ECE	E11-106R-0010945

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	8520	9890	11250	12790	14150	15510	17050
FROM 40 TO 25	9370	10870	12370	14050	15550	17050	18740
20	9560	11080	12610	14330	15860	17380	19110
12	9740	11300	12850	14620	16170	17720	19490
5	10310	11950	13600	15450	17110	18750	20610
*UPTO 5 CYC WITH FRONT LOADER	13120	15210	17310	19680	21770	23860	26230
5 HT	9560	11080	12610	14330	15860	17380	19110

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.