


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	126 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94021598	<b>RC (IN)</b>	160.7
<b>SW (IN)</b>	13.0	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	53.4	<b>RIM ALT</b>	W 9; W 10
<b>SLR (IN)</b>	24.4	<b>ECE</b>	E4-106R-000758

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	2060	2400	2740	3080	3420	3750
<b>25</b>	2060	2400	2740	3080	3420	3750
<b>20</b>	2220	2570	2930	3300	3660	4010
<b>5 LT</b>	2770	3220	3670	4120	4570	5030
<b>5 HT</b>	2220	2570	2930	3300	3660	4010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.