


# RIDEMAX IT 697 (M+S)

<b>TIRE SIZE</b>	<b>480/65 R 28 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	149 D ; 154 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	480	<b>RIM REC</b>	DW 15 L
<b>OD (MM)</b>	1335	<b>RIM ALT</b>	DW 14 L ; DW 16 L
<b>SLR (MM)</b>	615	<b>ECE</b>	E11-106R-006159
<b>RC (MM)</b>	4088	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2
65	1530	1885	2210	2570	2895	3250
50	1650	2035	2385	2775	3125	3510
40	1765	2175	2550	2965	3340	3750
30	1835	2260	2650	3080	3470	3900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.