


# AS 504

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>15.5/80 - 24</b>   |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       |  BIAS                    |
| <b>MACHINERY</b>          | LEVANTADOR TELESCÓPICO /<br>REBOQUE PARA OS CAMPOS /<br>IMPLEMENTOS AGRÍCOLAS /<br>LEVANTADOR TELESCÓPICO |
| <b>VERSÃO</b>             | SPECIAL   |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 148 A8  |
| <b>LI/SS FREE ROLLING</b> | 160 A8  |



## DIMENSÕES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94019458 | <b>RC (IN)</b> | 152.6           |
| <b>SW (IN)</b>    | 15.1     | <b>RIM REC</b> | W 12            |
| <b>OD (IN)</b>    | 49.7     | <b>RIM ALT</b> | W 13; W 14 L    |
| <b>SLR (IN)</b>   | 22.4     | <b>ECE</b>     | E11-106R-004614 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 51    |
|-----------|-------|
| 5 FR      | 13890 |
| 15 FR     | 11810 |
| 20 FR     | 11110 |
| 25 FR     | 9920  |
| 5 DW      | 9720  |
| 15 DW     | 8270  |
| 20 DW     | 7780  |
| 25 DW     | 6940  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.