

# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>300/95 R 52</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94029747	<b>RC (IN)</b>	227.3
<b>SW (IN)</b>	11.6	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	74.4	<b>RIM ALT</b>	W 10 ; W 11 ; DW 10 ; DW 11
<b>SLR (IN)</b>	35.0	<b>ECE</b>	E4-106R-001484

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	2980	3880	4720	5180	5480	6020	6550	7080	7600	-
25	2980	3880	4720	5180	5480	6020	6550	7080	7600	-
20	3190	4160	5060	5540	5870	6440	7010	7580	8150	-
5	3540	4450	5480	6500	7540	7760	8670	9590	10500	11410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.