


EARTHMAX SR 22 AS

TIRE SIZE	17.5 R 25
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PALA CARGADORA / MOTONIVELADORA
VERSIÓN	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	167 B ; 153 A8 ; 182 A2



DIMENSIONES US STANDARD

CÓDIGO USA	94069613	RIM REC	14.00/1.5
OD (IN)	53.1	TRA CODE	E2/G2/L2
SLR (IN)	23.4	STAR RATING	★★/★/★★
RC (IN)	157.9		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91
30	-	-	-	-	-	-	-	-	9650	10200	10500	11000	11400	12000	-	-	-	-
25	4080	4680	5200	5840	6400	6800	7400	8050	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	16100	16500	17100	17600	18200
MPH / PSI	94																	
30	-																	
25	-																	
5	18700																	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.