

# TR 135

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>23.1 - 26</b>   |
| <b>UM</b>        | IS STANDARD        |
| <b>MACHINERY</b> | TRAKTOR / SLÄPVAGN |
| <b>VERSION</b>   | HD                 |
| <b>TIRE TYPE</b> | TT                 |
| <b>LI/SS</b>     | 159 A6             |



## DIMENSIONER IS STANDARD

|                 |      |                 |                   |
|-----------------|------|-----------------|-------------------|
| <b>SW (MM)</b>  | 587  | <b>RIM REC</b>  | DW 20 B ; DW 20 A |
| <b>OD (MM)</b>  | 1585 | <b>PR</b>       | 16                |
| <b>SLR (MM)</b> | 700  | <b>SRI</b>      | 750               |
| <b>RC (MM)</b>  | 4615 | <b>TRA CODE</b> | R1                |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.30</b> |
| 30                | 4375        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.