


# FL 630 ULTRA

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>560/45 R 22.5</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ÉPANDEUR / VÉHICULE CITERNE /<br>REMORQUE / OUTILLAGE AGRICOLE                           |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 152 D ; 163 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 543  | <b>RIM REC</b> | AG 16.00        |
| <b>OD (MM)</b>  | 1076 | <b>ECE</b>     | E11-106R-003012 |
| <b>SLR (MM)</b> | 490  | <b>SRI</b>     | 525             |
| <b>RC (MM)</b>  | 3290 |                |                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70         | 1040 | 1185 | 1330 | 1650 | 1880 | 2170 | 2460 | 2690 | 2945 | 3235 |
| 65         | 1140 | 1300 | 1460 | 1815 | 2060 | 2380 | 2700 | 2950 | 3235 | 3550 |
| 50         | 1380 | 1575 | 1765 | 2195 | 2495 | 2885 | 3270 | 3570 | 3915 | 4300 |
| 40         | 1560 | 1780 | 2000 | 2490 | 2830 | 3270 | 3705 | 4050 | 4440 | 4875 |
| 30         | 1720 | 1960 | 2200 | 2740 | 3115 | 3595 | 4080 | 4455 | 4885 | 5365 |
| 25         | 1800 | 2055 | 2305 | 2865 | 3255 | 3760 | 4265 | 4660 | 5110 | 5610 |
| 10         | 2045 | 2335 | 2620 | 3260 | 3710 | 4285 | 4860 | 5305 | 5815 | 6390 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.