

AGRIMAX RT 855

TIRE SIZE	210/95 R 16
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	106 A8/B



DIMENSÕES US STANDARD

CÓDIGO USA	94028665	RC (IN)	94.0
SW (IN)	8.4	RIM REC	W 7
OD (IN)	31.7	RIM ALT	W 6 ; 6 LB
SLR (IN)	14.2	ECE	E4-106R-000608

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	990	1140	1300	1470	1640	1810	1950	2100
25	990	1140	1300	1470	1640	1810	1950	2100
20	1060	1220	1400	1580	1760	1940	2090	2250
5 LT	1320	1520	1750	1970	2190	2420	2620	2810
5 HT	1060	1220	1400	1580	1760	1940	2090	2250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.