

FLOTATION 558

TIRE SIZE	400/55 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊗ BIAS
MACHINERY	BALPRESS / SKÖRDEMASKIN / TANKBIL / SLÄPVAGN / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	140 A8/136 B
LI/SS FREE ROLLING	152 A8/148 B



DIMENSIONER IS STANDARD

SW (MM)	405	RIM REC	AG 11.75
OD (MM)	1020	RIM ALT	12.25; 13.00; AG 13.00
SLR (MM)	445	ECE	E4-106R-002262
RC (MM)	3084	PR	16

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70	3.80	4.00
10 FR	4745	4825	4970
20 FR	4270	4340	4475
30 FR	3795	3860	3975
40 FR	3390	3445	3550
50 FR	3050	3100	3150
10 DW	3345	3395	3500
20 DW	3010	3055	3150
30 DW	2675	2715	2800
40 DW	2390	2425	2500
50 DW	2150	2185	2240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.