


EARTHMAX SR 31

| | |
|---------------------|--|
| TIRE SIZE | 26.5 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ПОГРУЗЧИК / БУЛЬДОЗЕР / ШАРНИРНО-СОЧЛЕНЕННЫЙ САМОСВАЛ / ПОГРУЗЧИК / БУЛЬДОЗЕР |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 209 A2 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|--------------------|-----------|
| USA CODE | 94054381 | RIM REC | 22.00/3.0 |
| OD (IN) | 68.6 | TRA CODE | L3 |
| SLR (IN) | 30.2 | STAR RATING | ★★ |
| RC (IN) | 204.7 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 76 | 80 | 83 | 87 | 91 | 94 |
|-----------|-------|-------|-------|-------|-------|-------|
| 5 | 34200 | 35300 | 36400 | 37500 | 39700 | 40800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.