


FL 630 SUPER

TIRE SIZE	750/60 R 30.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ÉPANDÉUR / VÉHICULE CITERNE / REMORQUE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	181 D



DIMENSIONS US STANDARD

CODE USA	94041190	RC (IN)	201.4
SW (IN)	29.7	RIM REC	AG 24.00
OD (IN)	65.9	ECE	E4-106R-001499
SLR (IN)	29.4		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	5300	6130	6960	8450	9780	11260	12750	13750	15230	16560
40	5820	6730	7640	9280	10740	12370	14010	15100	16730	18190
30	7050	8160	9250	11230	13000	14970	16970	18280	20260	22010
25	7930	9160	10390	12620	14590	16820	19050	20530	22760	24730
15	9200	10640	12070	14660	16960	19540	22130	23850	26440	28740
5	10480	12120	13760	16700	19320	22270	25210	27180	30120	32740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.