

# FLOTATION 648

<b>TIRE SIZE</b>	<b>500/60 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	153 A8/149 B
<b>LI/SS FREE ROLLING</b>	165 A8/161 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94026364	<b>RC (IN)</b>	137.4
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	46.1	<b>RIM ALT</b>	15.00; 17.00
<b>SLR (IN)</b>	20.1	<b>ECE</b>	E11-106R-004390

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	49	51	52
<b>5 FR</b>	15370	15630	15890
<b>10 FR</b>	13830	14060	14310
<b>20 FR</b>	12300	12510	12720
<b>25 FR</b>	10980	11170	11350
<b>30 FR</b>	9880	10050	10200
<b>5 DW</b>	10890	11080	11260
<b>10 DW</b>	9810	9980	10140
<b>20 DW</b>	8720	8860	9020
<b>25 DW</b>	7780	7910	8050
<b>30 DW</b>	7000	7120	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.