

# AGRIMAX RT 657

|                  |                                          |
|------------------|------------------------------------------|
| <b>TIRE SIZE</b> | <b>600/65 R 38</b>                       |
| <b>UM</b>        | US STANDARD                              |
| <b>MACHINERY</b> | VINEYARD HARVESTER / TRACTOR / HARVESTER |
| <b>VERSION</b>   | SPECIAL                                  |
| <b>TL/TT</b>     | TL                                       |
| <b>LI/SS</b>     | 159 D ; 162 A8                           |



## DIMENSIONS US STANDARD

|                 |          |                                      |                |
|-----------------|----------|--------------------------------------|----------------|
| <b>USA CODE</b> | 94066612 | <b>RIM REC</b>                       | DW 20 B        |
| <b>SW (IN)</b>  | 24.1     | <b>RIM ALT</b>                       | W 18 L         |
| <b>OD (IN)</b>  | 68.7     | <b>ECE</b>                           | E4-106R-000623 |
| <b>SLR (IN)</b> | 31.1     | <b>TRA CODE</b>                      | R1W            |
| <b>RC (IN)</b>  | 206.6    | <b>TREAD DEPTH (32<sup>nd</sup>)</b> | 68.67          |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23    | 29    | 35    |
|-------------|------|------|------|------|------|-------|-------|-------|
| <b>40</b>   | 4630 | 5400 | 6080 | 6760 | 7430 | 8010  | 8870  | 9650  |
| <b>30</b>   | 4870 | 5680 | 6380 | 7100 | 7800 | 8410  | 9330  | 10130 |
| <b>25</b>   | 5030 | 5860 | 6600 | 7330 | 8070 | 8700  | 9630  | 10470 |
| <b>20</b>   | 5330 | 6220 | 7000 | 7770 | 8550 | 9210  | 10220 | 11100 |
| <b>5 LT</b> | 6220 | 7240 | 8150 | 9060 | 9960 | 10740 | 11900 | 12930 |
| <b>5 HT</b> | 5330 | 6220 | 7000 | 7770 | 8550 | 9210  | 10220 | 11100 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.