

# AW 711

<b>TIRE SIZE</b>	<b>380/55 R 16.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	150 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	360	<b>RIM REC</b>	12
<b>OD (MM)</b>	830	<b>RIM ALT</b>	11.75
<b>SLR (MM)</b>	372	<b>ECE</b>	E4-106R-001393
<b>RC (MM)</b>	2500	<b>SRI</b>	390

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
50	1005	1310	1610	1845	2145	2450	2615	2885	3150	3350
40	1005	1310	1610	1845	2145	2450	2615	2885	3150	3350
30	1130	1465	1805	2070	2405	2745	2930	3230	3530	3755
25	1200	1560	1920	2195	2555	2915	3115	3435	3755	3990
20	1270	1650	2030	2325	2705	3085	3300	3635	3975	4225
10	1410	1830	2255	2580	3005	3425	3660	4035	4410	4690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.