


AGRIMAX SPARGO

TIRE SIZE	VF 480/80 R 50 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	179 D



DIMENSIONES IS STANDARD

SW (MM)	479	RIM REC	DW 16 L
OD (MM)	2038	RIM ALT	DW 15 L
SLR (MM)	947	ECE	E11-106R-004757
RC (MM)	6224	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6
70	3945	4370	4790	5005	5285	5425	5565	5850	6130	6345	6625	6835	7050
FROM 65 TO 40	4340	4805	5270	5500	5810	5965	6120	6430	6740	6975	7285	7515	7750
30	4425	4900	5375	5610	5925	6085	6240	6560	6875	7110	7430	7665	7905
20	4510	4995	5480	5720	6045	6205	6365	6685	7010	7250	7575	7815	8060
10*	4770	5285	5795	6050	6390	6560	6730	7075	7415	7670	8010	8265	8525
UPTO 15 CYC.	5885	6515	7145	7460	7880	8090	8300	8720	9140	9455	9875	10190	10505
UPTO 30 CYC.	4930	5460	5985	6250	6600	6775	6950	7305	7655	7920	8275	8535	8800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.