

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 520/70 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 150 D |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94062317 | RC (IN) | 208.7 |
| SW (IN) | 20.3 | RIM REC | W 16 L |
| OD (IN) | 68.9 | RIM ALT | W 15 L; W 18 L |
| SLR (IN) | 31.2 | ECE | E11-106R-005525 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 40 | 4070 | 4730 | 5400 | 6060 | 6720 | 7390 |
| 30 | 4280 | 4970 | 5670 | 6370 | 7070 | 7760 |
| 25 | 4450 | 5180 | 5910 | 6640 | 7360 | 8090 |
| 20 | 4680 | 5450 | 6210 | 6980 | 7740 | 8500 |
| 5 LT | 5450 | 6340 | 7230 | 8120 | 9020 | 9900 |
| 5 HT | 4680 | 5450 | 6210 | 6980 | 7740 | 8500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.