

# AW 702

<b>TIRE SIZE</b>	12.5/80 - 15.3
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	146 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	312	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	885	<b>ECE</b>	E11-106R-004356
<b>SLR (MM)</b>	387	<b>PR</b>	18
<b>RC (MM)</b>	2593		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	5.50
10 FR	4200
25 FR	3570
30 FR	3360
40 FR	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.