


MULTIMAX MP 527

| | |
|---------------------|--|
| TIRE SIZE | 400/80 R 24 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 162 A8/B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|---------------------------|
| SW (MM) | 404 | RIM REC | DW 13 |
| OD (MM) | 1250 | RIM ALT | DW 12 ; DW 13 L ; DW 14 L |
| SLR (MM) | 578 | ECE | E11-106R-002982 |
| RC (MM) | 3834 | SRI | 600 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.4 | 3.6 | 4.0 | 4.4 | 4.6 | 4.8 | 5.0 | 5.2 | 5.4 |
|------------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|
| 50 | 1855 | 2185 | 2565 | 2900 | 3230 | 3350 | 3520 | 3895 | 4220 | 4435 | 4540 | 4750 | - | - |
| 40 | 1855 | 2185 | 2565 | 2900 | 3230 | 3350 | 3520 | 3895 | 4220 | 4435 | 4540 | 4750 | - | - |
| 30 | 1985 | 2340 | 2750 | 3105 | 3460 | 3590 | 3770 | 4170 | 4515 | 4745 | 4860 | 5085 | - | - |
| 25 | 2060 | 2430 | 2850 | 3220 | 3590 | 3725 | 3910 | 4330 | 4690 | 4925 | 5040 | 5275 | - | - |
| 10 CYC. | 2280 | 2785 | 3280 | 3850 | 4350 | 4600 | 4845 | 5280 | 5845 | 6090 | 6330 | 6655 | 6810 | 7125 |
| STATIC | 3500 | 4270 | 5030 | 5900 | 6670 | 7050 | 7430 | 8100 | 8960 | 9340 | 9710 | 10205 | 10445 | 10925 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.