

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/50 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	DUAL BEAD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	156 A8/152 B
<b>LI/SS FREE ROLLING</b>	169 A8/165 B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94045266	<b>RC (IN)</b>	137.8
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E11-106R-004392
<b>SLR (IN)</b>	20.1	<b>PR</b>	20

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44	45	46
<b>5 FR</b>	17240	17580	17900
<b>10 FR</b>	15510	15820	16110
<b>20 FR</b>	13790	14060	14320
<b>25 FR</b>	12310	12550	12790
<b>30 FR</b>	11080	11300	11350
<b>5 DW</b>	11880	12110	12350
<b>10 DW</b>	10690	10900	11110
<b>20 DW</b>	9500	9690	9880
<b>25 DW</b>	8490	8650	8820
<b>30 DW</b>	7640	7790	7830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.