

EARTHMAX SR 49 M



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 49 M



EARTHMAX SR 49 M is an All Steel radial tire with a special non-directional pattern designed for load haul dumps (LHD), low profile dump trucks (LPDT), loaders and dozers operating in severe rocky conditions primarily in underground mining. EARTHMAX SR 49 M is ideal for severe operations requiring exceptional traction and stability.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø25"	26.5 R 25	TL	SH4	****	-	22.00/3.0	-	0	27.9	70.2	31.5	208.5	70.56	CR
	29.5 R 25	TL	E4/L4	**	200 B 216 A2	25.00/3.5	-	151	30.7	75.0	33.2	220.5	71.82	CR
	29.5 R 25	TL	E4/L4	****/**	-	25.00/3.5	-	0	30.7	75.0	33.2	220.5	71.82	CR
	29.5 R 25	TL	L4	**	216 A2	25.00/3.5	-	0	30.7	75.0	33.2	220.5	71.82	CR
	26.5 R 25	TL	E4/L4	**/*	193 B 202 A2	22.00/3.0	-	113	27.9	70.2	31.5	208.5	70.56	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			
		Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index	

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
29.5 R 25	TL	E4/L4	**/*	200 B 208 A2	25.00/3.5	-	151	30.7	75.0	33.2	220.5	71.82	CR
29.5 R 25	TL	SH4	****	-	25.00/3.5	-	0	30.7	75.0	33.2	220.5	71.82	CR
26.5 R 25	TL	E4/L4	****/**	-	22.00/3.0	-	0	27.9	70.2	31.5	208.5	70.56	CR
29.5 R 25	TL	L4	*	208 A2	25.00/3.5	-	0	30.7	75.0	33.2	220.5	71.82	CR
26.5 R 25	TL	L4	*	202 A2	22.00/3.0	-	0	27.9	70.2	31.5	208.5	70.56	CR
26.5 R 25	TL	L4	**	209 A2	22.00/3.0	-	0	27.9	70.2	31.5	208.5	70.56	CR
29.5 R 29	TL	SH4	****	-	25.00/3.5	24.00/3.5 26.00/3.5	0	30.9	79.0	35.7	248.8	75.6	CR
29.5 R 29	TL	L4	***	223 A2	25.00/3.5	24.00/3.5 26.00/3.5	0	30.9	79.0	35.7	248.8	75.6	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			
E4/L4/SH4		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	
B			
223 lbs			

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026