


# AW 711

<b>TIRE SIZE</b>	<b>340/60 R 16.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN / ARBETSFORDON / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	145 A8/B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94044788	<b>RC (IN)</b>	97.5
<b>SW (IN)</b>	12.8	<b>RIM REC</b>	11
<b>OD (IN)</b>	32.3	<b>ECE</b>	E4-106R-001392
<b>SLR (IN)</b>	14.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	73
30	1920	2500	3080	3520	4100	4670	4990	5500	6020	6390
25	1920	2500	3080	3520	4100	4670	4990	5500	6020	6390
20	2150	2800	3440	3950	4590	5240	5590	6160	6730	7160
15	2290	2980	3660	4200	4880	5570	5940	6560	7160	7620
10	2420	3150	3870	4440	5160	5890	6290	6930	7580	8060
5	2690	3490	4300	4930	5730	6540	6990	7700	8420	8950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.