

# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>710/70 R 42</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | BESPRUTNINGSBIL / TRAKTOR /<br>SKÖRDEMASKIN FÖR VINGÅRD /<br>SKÖRDEMASKIN / ARBETSFORDON |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 173 D ; 176 A8   |



## DIMENSIONER IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 716  | <b>RIM REC</b> | DW 23 B        |
| <b>OD (MM)</b>  | 2061 | <b>RIM ALT</b> | DW 25 B        |
| <b>SLR (MM)</b> | 922  | <b>ECE</b>     | E4-106R-000807 |
| <b>RC (MM)</b>  | 6174 | <b>SRI</b>     | 975            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 3120 | 3640 | 4095 | 4550 | 5005 | 5395 | 5980 | 6500 |
| 50         | 3280 | 3825 | 4300 | 4780 | 5260 | 5665 | 6280 | 6825 |
| 40         | 3410 | 3980 | 4475 | 4970 | 5470 | 5895 | 6535 | 7100 |
| 30         | 3590 | 4190 | 4710 | 5235 | 5760 | 6205 | 6880 | 7475 |
| 10 LT      | 4185 | 4880 | 5490 | 6100 | 6710 | 7230 | 8015 | 8710 |
| 10 HT      | 3590 | 4190 | 4710 | 5235 | 5760 | 6205 | 6880 | 7475 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.