

AGRIMAX RT 657



AGRIMAX
RADIAL TRACTOR TIRES

AGRIMAX RT 657



AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.



	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø16"	320/65 R 16	117 D 120 A8	W 10	W 9 W 11	12.6	32.4	14.4	97.1	390	STD
Ø18"	340/65 R 18	113 A8/B	W 11	W 10 W 12	13.5	35.4	15.7	105.0	425	STD
	320/65 R 18	125 A8/B	W 10	W 9 W 11	12.2	34.8	15.7	105.0	425	STD
	320/65 R 18	109 A8/B	W 10	W 9 W 11	12.6	34.4	15.4	101.9	425	STD
Ø20"	420/65 R 20	135 D 138 A8	W 13	W 11 W 12	16.5	41.5	18.4	124.5	500	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			
			
D	181 lbs		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	440/65 R 20	138 D 141 A8	W 14 L	W 13 W 15 L	17.4	42.5	18.9	127.6	525	STD
	340/65 R 20	124 D 127 A8	W 11	W 10 W 12	13.5	37.4	16.9	113.9	450	STD
Ø24"	440/65 R 24	135 D 138 A8	W 14 L	W 13 W 15 L	17.4	46.5	21.2	139.6	575	STD
	480/65 R 24	140 D 143 A8	W 15 L	W 14 L	18.9	48.6	22.1	146.9	600	SPL
	540/65 R 24	146 D 149 A8	W 16 L	W 18 L	20.9	51.7	23.5	155.2	625	STD
	540/65 R 24	146 D 149 A8	W 16 L	W 18 L	20.9	51.7	23.2	154.7	625	SPL
	440/65 R 24	135 D 138 A8	W 14 L	W 13 W 15 L	17.4	46.5	21.2	139.6	575	SPL
	420/65 R 24	138 D 141 A8	W 13	W 11 W 12	16.5	45.5	20.4	136.5	550	STD
	480/65 R 24	140 D 143 A8	W 15 L	W 14 L	18.9	48.6	22.1	146.9	600	STD
Ø28"	540/65 R 28	149 D 152 A8	W 16 L	W 18 L	20.9	55.6	25.3	167.4	675	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
480/65 R 28	142 D 145 A8	W 15 L	W 14 L	18.9	52.6	24.0	161.1	650	STD
600/65 R 28	154 D 157 A8	DW 20 B	W 18 L	24.1	58.7	26.4	176.0	700	STD
420/65 R 28	135 D 138 A8	W 13	W 12 W 11	16.5	49.5	23.0	150.6	600	STD
540/65 R 28	149 D 152 A8	W 16 L	W 18 L	20.9	55.6	25.3	167.4	675	SPL
440/65 R 28	138 D 141 A8	W 14 L	W 13 W 15 L	17.4	50.5	23.2	154.6	625	STD
600/65 R 28	154 D 157 A8	DW 20 B	W 18 L	24.1	58.7	26.4	176.0	700	SPL
540/65 R 30	150 D 153 A8	W 16 L	W 18 L	20.9	57.6	26.4	173.3	700	SPL
420/65 R 30	136 D 139 A8	W 13	W 12 W 11	16.5	51.5	23.9	155.6	625	STD
600/65 R 30	155 D 158 A8	DW 20 B	W 18 L	24.1	60.7	27.4	181.5	725	STD
540/65 R 30	150 D 153 A8	W 16 L	W 18 L	20.9	57.6	26.4	173.3	700	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			
			
D	181 lbs		

Permissible tolerances: 0.0. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø34"	540/65 R 34	152 D 155 A8	W 16 L	W 18 L	20.9	61.7	28.0	186.7	750	SPL
	540/65 R 34	152 D 155 A8	W 16 L	W 18 L	20.9	61.7	28.0	186.7	750	STD
	600/65 R 34	157 D 160 A8	DW 20 B	W 18 L	24.1	64.7	29.2	195.3	775	STD
	600/65 R 34	157 D 160 A8	DW 20 B	W 18 L	24.1	64.7	29.2	195.3	775	SPL
Ø38"	540/65 R 38	153 D 156 A8	W 16 L	W 18 L	20.9	65.6	29.9	199.2	800	SPL
	600/65 R 38	159 D 162 A8	DW 20 B	W 18 L	24.1	68.7	31.1	206.6	825	SPL
	650/65 R 38	163 D 166 A8	DW 20 B	DW 21 B DW 23 B	25.4	71.3	32.7	215.9	875	STD
	650/65 R 38	163 D 166 A8	DW 20 B	DW 21 B DW 23 B	25.4	71.3	32.7	215.9	875	SPL
	900/55 R 38	179 D 181 A8	DW 27 B	DW 30 B	34.6	76.8	34.6	230.0	925	STD
	600/65 R 38	159 D 162 A8	DW 20 B	W 18 L	24.1	68.7	31.1	206.6	825	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			
R1W			
D	181 lbs		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
650/65 R 38	178 A8 175 B	DW 20 B	DW 21 B DW 23 B	25.4	71.5	32.6	216.1	875	SB
540/65 R 38	153 D 156 A8	W 16 L	W 18 L	20.9	65.6	29.9	199.2	800	STD
	650/65 R 42	165 D 168 A8	DW 20 B DW 21 B DW 23 B	25.4	75.3	34.6	228.7	925	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index