

# AW 09

<b>TIRE SIZE</b>	<b>300/80 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / CEIFEIRA
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	120 A8
<b>LI/SS FREE ROLLING</b>	132 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	295	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	860	<b>ECE</b>	E4-106R-000375
<b>SLR (MM)</b>	376		
<b>RC (MM)</b>	2520		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.80</b>
10 FR	2800
25 FR	2380
30 FR	2240
40 FR	2000
10 DW	1960
25 DW	1665
30 DW	1570
40 DW	1400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.