


FL 630 SUPER

| | |
|---------------------|--|
| TIRE SIZE | 650/65 R 30.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPREADER / TANKER / TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 176 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94045594 | RC (IN) | 195.9 |
| SW (IN) | 25.4 | RIM REC | AG 20.00 |
| OD (IN) | 63.8 | ECE | E4-106R-001653 |
| SLR (IN) | 28.9 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 4560 | 5280 | 6000 | 7270 | 8410 | 9700 | 10980 | 11840 | 13120 | 14250 |
| 40 | 5020 | 5800 | 6580 | 7990 | 9240 | 10650 | 12060 | 13000 | 14410 | 15650 |
| 30 | 6070 | 7020 | 7960 | 9670 | 11190 | 12890 | 14590 | 15730 | 17440 | 18950 |
| 25 | 6820 | 7890 | 8950 | 10870 | 12570 | 14480 | 16400 | 17680 | 19600 | 21300 |
| 15 | 7930 | 9160 | 10390 | 12620 | 14590 | 16820 | 19050 | 20530 | 22760 | 24730 |
| 5 | 9020 | 10430 | 11840 | 14370 | 16630 | 19170 | 21700 | 23390 | 25920 | 28170 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.