


AGRIMAX V- FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 600/70 R 30 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MOTORSTARK TRAKTOR / TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 168 D |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94064601 | RC (IN) | 185.5 |
| SW (IN) | 23.7 | RIM REC | DW 21 B |
| OD (IN) | 63.1 | RIM ALT | DW 20 B |
| SLR (IN) | 27.6 | ECE | E11-106R-006162 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 |
|--------------------------------------|------|-------|-------|-------|-------|-------|-------|
| 45 | 5610 | 6500 | 7410 | 8420 | 9310 | 10220 | 11230 |
| FROM 40 TO 25 | 6170 | 7150 | 8150 | 9260 | 10240 | 11230 | 12350 |
| 20 | 6290 | 7290 | 8300 | 9440 | 10440 | 11450 | 12590 |
| 12 | 6420 | 7430 | 8470 | 9620 | 10650 | 11670 | 12830 |
| 5 | 6790 | 7860 | 8950 | 10180 | 11250 | 12350 | 13580 |
| *UPTO 5 CYC WITH FRONT LOADER | 8640 | 10010 | 11400 | 12960 | 14330 | 15720 | 17280 |
| 5 HT | 6290 | 7290 | 8300 | 9440 | 10440 | 11450 | 12590 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.