


AGRIMAXFACTOR

| | |
|---------------------|--|
| TIRE SIZE | 600/70 R 30 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 152 D ; 155 A8 |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94070152 | RC (IN) | 187.6 |
| SW (IN) | 24.1 | RIM REC | DW 20 B |
| OD (IN) | 63.1 | RIM ALT | DW 18 L; W 18 L |
| SLR (IN) | 28.4 | ECE | E11-106R-007524 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|-------|
| 40 | 4310 | 5020 | 5720 | 6430 | 7130 | 7830 |
| 30 | 4530 | 5270 | 6010 | 6750 | 7480 | 8220 |
| 25 | 4710 | 5470 | 6240 | 7010 | 7780 | 8540 |
| 20 | 4960 | 5760 | 6580 | 7390 | 8200 | 9010 |
| 5 LT | 5780 | 6720 | 7660 | 8610 | 9560 | 10490 |
| 5 HT | 4960 | 5760 | 6580 | 7390 | 8200 | 9010 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.