

AGRIMAX FORCE

TIRE SIZE	IF 650/65 R 38 CFO
UM	US STANDARD
MACHINERY	ERNTemaschine / HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	169 D



ABMESSUNGEN US STANDARD

USA-CODE	94059225	RIM REC	DW 23 B
SW (IN)	25.6	ECE	E11-106R-005103
OD (IN)	72.0	TRA CODE	R1W
SLR (IN)	32.7	TREAD DEPTH (32 nd)	73.08
RC (IN)	216.9		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5460	6390	7320	8130	8950	9640	10800	11630
FROM 40 TO 25	6010	7030	8050	8950	9840	10600	11880	12790
20	6240	7310	8370	9300	10230	11020	12360	13290
12	6480	7590	8690	9660	10630	11440	12830	13800
5	7630	8930	10220	11360	12500	13460	15090	16240
UPTO 20 CYC	7800	9140	10460	11630	12790	13780	15440	16620
UPTO 10 CYC	9300	10890	12470	13870	15260	16430	18410	19820
UPTO 5 CYC	10210	11950	13680	15210	16730	18020	20190	21740
10HT	6240	7310	8370	9300	10230	11020	12360	13290

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.