

XL GRIP PLUS



XL GRIP PLUS

XL GRIP PLUS (L-4) has been specially designed for loaders. Its deep tread provides high cut and puncture resistance as well as an extended tyre life-cycle. XL GRIP PLUS is particularly suitable for heavy-duty service.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	29.5 - 25	TL	L4	32	-	25.00/3.5	-	0	760	1915	876	5709	59,5	STD
	29.5 - 25	TL	L4	36	-	25.00/3.5	-	0	760	1915	876	5709	59,5	STD
	29.5 - 25	TL	L4	28	-	25.00/3.5	-	0	760	1915	876	5709	59,5	STD
	26.5 - 25	TL	L4	28	-	22.00/3.0	-	0	690	1775	815	5253	57,5	STD

STD: STANDARD

TECHNOLOGIES			PERFORMANCES				
							
L4							

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (mm) 	OD (mm) 	SLR (mm) 	RC (mm) 	TREAD DEPTH (mm)	VERSION
						REC RIM	ALT RIM							
														
	26.5 - 25	TL	L4	32	-	22.00/3.0	-	0	690	1775	815	5253	57,5	STD
Ø33"	35/65 -33	TL	L4	42	-	28.00/3.5	-	0	900	2080	0	0	62,5	STD

STD: STANDARD



TECHNOLOGIES					PERFORMANCES				
									
		-	-	-	-	-	-	-	-

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026