


# EARTHMAX SR 35

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 775/65 R 29                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | CHARGEUR / CHARGEUR / CHARGEUR                                                           |
| VERSION      | CUT RESISTANT COMPOUND                                                                   |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 206 A2                                                                                   |



## DIMENSIONS IS STANDARD

|          |           |             |                      |
|----------|-----------|-------------|----------------------|
| OD (MM)  | 1752      | RIM ALT     | 24.00/3.0; 25.00/3.5 |
| SLR (MM) | 787       | TRA CODE    | L3                   |
| RC (MM)  | 5311      | STAR RATING | ★                    |
| RIM REC  | 24.00/3.5 |             |                      |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00  | 4.25  | 4.50  | 4.75  |
|------------|-------|-------|-------|-------|
| 10         | 15000 | 15500 | 16500 | 17000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.